



4300 Loftwood Drive
Cohutta, GA 30710
Phone: 1-800-710-8422
Phone: (706) 694-6418
Fax: (706) 694-8158
info@welinternational.com
www.welinternational.com

AXMINSTER CARPET SPECIFICATION
Density: 7 X 12

1. Item: Axminster Carpets
 2. Width Available: 3.63m (11'10 7/8"), 3.66m (12'), and 4.00m (13'1 1/2")
 3. Type: Woven Jacquard Axminster
 4. Face Yarn: 80% British and New Zealand Wool, 20% Ascend Type 6.6 Nylon
 5. Rows: 12 / inch
 6. Pitch: 7 / inch
 7. Pile Height: 0.276", 7mm; Total Height: 10mm
 8. Yarn Ply & count: 2 Ply - 2/42
 9. Yarn Weight: Total Pile Weight: 57.96 ounces
 10. Primary Backing: Weft: Polypropylene; Warp: Polyester
 11. Secondary Backing: SBR Conductive Abrasion Resistant Latex
 12. Total Weight: 91 ounces
- Fire Classification Class I.
13. Performance:
 - a. Critical radiation flux (ASTME648): Class I
 - b. Tuft Bind (WNZ TM 202): >10N
 - c. Insect resistance: (WNZTM 27): Class 5
 - d. Color Fastness against light (ISO4892-2: 1994): >Class 4
 - e. Electric Propensity (AATCC134): <3.5KV
 - f. Thickness loss under static loading (WNZTM124A): minimum 80% thickness recovery, after 24 hours removal of load
 - g. Thickness loss under dynamic loading: 1000 impact (GB/T14252-93) average rate of loss <15%
 - h. Hexapod appearance change after 12000 revolutions (WNZTM 247/251/284): Min 3