



Woven Vinyl Flooring Technical Data

TEST

ISO-4892-2-Xenon Arc Lamp - Light Fades

Outdoor/Indoor use

FVM SS/CUMSS 302 Flammability

Non-flammable

ASTM-D-5252 Hexapod Drum Test - Surface Appearance

Durable

ASTM C-1028 Static Coefficient & Friction - Dry

ASTM C-1028 Static Coefficient & Friction - Wet

Safe from slippage

ASTM F-925 Std. Test Resistance to Chemical

Stain Resistant

ASTM D7570 – Dimensional Stability

Dimensionally stable

AATCC Test Method 129 Color Fastener to Ozone under high humidity. No. Cycles 8

Color fast to high heat and humidity conditions

Water Penetration Impact Test

10,000 cycles @ 10 lbs. per sq. in.

Impervious to moisture penetration

RESULTS

Rating 5 - Negligible/No Change

Approved – meets or exceeds

Federal Motor Vehicle Safety Std. No. 302 (NHTSA.DOT)

4.5 Negligible/Slight Change

Average .81

Average .95

White Vinegar – No change

Rubbing Alcohol – No change

White Mineral Oil – No change

Sodium hydroxide solution – No change

Hydrochloric acid solution – No change

Sulfuric acid solution – No change

Household ammonia solution – No change

Household bleach solution – No change

Olive Oil – No change

Kerosene – No change

Unleaded gasoline – No change

Phenol – No change

Machine Direction – Average +0.199%

Cross Direction – Average -0.115%

Rating 5 - Negligible/No Change

No penetration occurred